

MAIN CAMPUS San Roque, Sogod, Southern Leyte Email: <u>president@southernleytestateu.edu.ph</u> Website: www.southernleytestateu.edu.ph

Excellence | Service | Leadership and Good Governance | Innovation | Social Responsibility | Integrity | Professionalism | Spirituality



## SUPPLEMENTAL/BID BULLETIN No. 01

### Supply, Delivery and Installation of ICT Equipment and Peripherals

This Supplemental/Bid Bulletin No. 01 for the abovementioned project is issued to modify or amend the items in the Bidding Documents. This shall form an integral part of the Bid Documents.

TECHNICAL SPECIFICATIONS		
REFERENCE	AMENDMENT	
<b>Ітем #3</b> UPS (Smart UPS 3000VA LCD 230	Ітем #3	
w/SmartConnect)		
	UPS (Online Tower Type UPS)	
	Input 110Vac~300Vac**	
	Frequency 45Hz~65Hz	
	Phase Single Phase with Ground	
	Output	
	Capacity <b>3000VA/2700W</b>	
	Voltage 200/208/220/230/240	
	Frequency 3Hz or 1Hz (selectable)	
	Harmonic Distortion <3% (at full linear load)	
	Current Crest Factor 3:1	
	Transfer Time (AC to DC) 0ms	
	Efficiency 90%	
	Waveform Pure Sine Wave	
	Battery	
	Number of Batteries 6pcs	
	Type & Capacity Sealed Lead Acid Maintenance	
	Free, 12V/7AH or 12V/9AH upon request	
	Rated Battery Voltage 72Vdc	
	Display	
	LCD Input Voltage / Input Frequency / Output	
	Voltage / Output Frequency / Load Percentage /	
	Battery Voltage / Temperature	
	Alarms	
	Audible and Visual Line Failure, Battery Low,	
	Transfer to Bypass, System Fault Conditions	
1	· · · · · · · · · · · · · · · · · · ·	



# Southern Leyte State University

MAIN CAMPUS San Roque, Sogod, Southern Leyte Email: <u>president@southernleytestateu.edu.ph</u> Website: www.southernleytestateu.edu.ph

Excellence | Service | Leadership and Good Governance | Innovation | Social Responsibility | Integrity | Professionalism | Spirituality

	Full Protection Overload, Over Temperature, Short Circuit, Discharge, Overcharge Special Features DC Start Yes <b>Physical</b> Dimension, W x D x H (mm) 189x444x322 Weight (kg) 19 Outlets*** 1x Schuko +3x IEC-C13 <b>Interface</b> Communication Port Standard: USB and RS232
Item # 9 Wi-Fi Duplex All-in-One Ink Tank Printer	Item # 9 Wi-Fi Duplex All-in-One Ink Tank Printer
<ul> <li>Specifications:</li> <li>Printer Type: Print, Scan, Copy, Fax with ADF</li> <li>Minimum Ink Droplet Volume: 3.8 pl</li> <li>Print Direction: Bi-directional printing</li> <li>Nozzle Configuration: 800 x 1 nozzles Black, 256 x 1 nozzles per colour (Cyan, Magenta, Yellow)</li> <li>Maximum Resolution: 4800 x 2400 dpi</li> <li>Automatic 2-sided Printing: Yes (up to A3)</li> <li>Print Speed:</li> <li>Photo Default - 10 x 15 cm / 4 x 6 " *1: Approx. 43 sec per photo (Border) / 52 sec per photo (Borderless)*2</li> <li>Draft, A4 (Black / Colour): Up to 32.0 ppm / 22.0 ppm *2</li> <li>ISO 24734, A4 Simplex (Black / Colour): Up to 25.0 ipm / 12.0 ipm *2</li> <li>ISO 24734, A4 Simplex (Black / Colour): Up to 16.0 ipm / 9.0 ipm *2</li> <li>ISO 24734, A3 Simplex (Black / Colour): Up to 13.5 ipm / 6.0 ipm *2</li> <li>ISO 24734, A3 Duplex (Black / Colour): Up to 10.0 ipm / 5.0 ipm *2</li> <li>ISO 24734, A3 Duplex (Black / Colour): Up to 10.0 ipm / 5.0 ipm *2</li> <li>ISO 29183, A4 Simplex Flatbed (Black / Colour): Up to 23.0 ipm / 10.0 ipmISO 24735, A4 Simplex Flatbed (Black / Colour): Up to 23.0 ipm / 10.0 ipmISO 24735, A4 Simplex ADF (Black / Colour): Up to 15.5 ipm / 7.5 ipm</li> </ul>	<ul> <li>Specifications:</li> <li>Printer Type: Print, Scan, Copy, Fax with ADF</li> <li>Minimum Ink Droplet Volume: 3.8 pl</li> <li>Print Direction: Bi-directional printing</li> <li>Nozzle Configuration: 800 x 1 nozzles Black, 256 x 1 nozzles per colour (Cyan, Magenta, Yellow)</li> <li>Maximum Resolution: 4800 x 2400 dpi</li> <li>Automatic 2-sided Printing: Yes (up to A3)</li> <li>Print Speed:</li> <li>Photo Default - 10 x 15 cm / 4 x 6 " *1: Approx. 43 sec per photo (Border) / 52 sec per photo (Borderless)*2</li> <li>Draft, A4 (Black / Colour): Up to 32.0 ppm / 22.0 ppm *2</li> <li>ISO 24734, A4 Simplex (Black / Colour): Up to 25.0 ipm / 12.0 ipm *2</li> <li>ISO 24734, A4 Duplex (Black / Colour): Up to 16.0 ipm / 9.0 ipm *2</li> <li>ISO 24734, A3 Simplex (Black / Colour): Up to 13.5 ipm / 6.0 ipm *2</li> <li>ISO 24734, A3 Duplex (Black / Colour): Up to 10.0 ipm / 5.0 ipm *2</li> <li>ISO 24734, A3 Simplex (Black / Colour): Up to 10.0 ipm / 5.0 ipm *2</li> <li>ISO 24734, A3 Simplex (Black / Colour): Up to 10.0 ipm / 5.0 ipm *2</li> <li>ISO 24734, A3 Simplex (Black / Colour): Up to 10.0 ipm / 5.0 ipm *2</li> <li>ISO 24734, A3 Duplex (Black / Colour): Up to 10.0 ipm / 5.0 ipm *2</li> <li>Copy Function:</li> <li>Reduction / Enlargement:25 - 400%Maximum Copy Size:A3Copy Resolution:600 x 600 dpiMax</li> <li>Copies:999 copies</li> <li>ISO 29183, A4 Simplex Flatbed (Black / Colour): Up to 23.0 ipm / 10.0 ipmISO 24735, A4 Simplex ADF (Black / Colour): Up to 15.5 ipm / 7.5 ipm</li> </ul>
Scanner Type: Sheet-fed, one-pass duplex color scanner	Scanner Type: Flatbed colour image scanner Sensor Type: CIS



# Southern Leyte State University

MAIN CAMPUS San Roque, Sogod, Southern Leyte Email: <u>president@southernleytestateu.edu.ph</u> Website: www.southernleytestateu.edu.ph

Excellence | Service | Leadership and Good Governance | Innovation | Social Responsibility | Integrity | Professionalism | Spirituality

Photoelectric Device: CMOS single-line contact image	Optical Resolution:1200 x 2400 dpi
sensor	Maximum Scan Area:297 x 431.8 (mm)
Optical Resolution: 600 dpi	Scanner Bit Depth (Colour):48-bit input, 24-bit output
Color Bit Depth: 48-bits per pixel internal / 24-bit	Scanner Bit Depth (Grayscale):16-bit input, 8-bit
external	output
Monochrome Bit Depth: 1-bit	Scanner Bit Depth (Black & White):16-bit input, 1-bit
Grayscale Bit Depth: 16-bits per pixel internal / 8-bit	output
external	Scan Speed (Flatbed / ADF (Simplex   Duplex)):
Output Resolution: 75 to 1200 dpi	200dpi, Black: 5 sec / Up to 26.0 ipm   11.5 ipm
Effective Pixels: 5,100 x 21,600 pixels	
	200dpi, Colour: 10 sec / Up to 9.0 ipm   6.0 ipm
Light Source: 3-Color RGB LED	E au Europhian
Scanning Speed: up to 26 ppm/52 ipm1	Fax Function:
Scan Features: Buttons: 3 buttons: Power, Start, and	Type Of Fax: Walk-up Black-and-white and Colour Fax
Stop	Capability
Power: Rated Voltage: 100 â⊠" 240 VAC	Receive Memory / Page Memory:6MB, Page memory
Rated Frequency: 50 â <sup>™</sup> 60 Hz	Up to 550 pages
Power Consumption:	Error Correction Mode:
Normal mode: 18 W	ITU-T T.30
Ready mode: 7 W	Fax Speed (Data Transfer Rate):Up to 33.6 kbps,
Sleep mode: 1.6 W	Approx. 3 sec/page
Off: 0.4 W	Fax Resolution : Up to 200 x 200 dpi
Automatic Document Feeder: Capacity: 50 sheets	Transmission Paper Size (Flatbed):A5, A4, A3, B5, B4,
Document Sizes: Paper size Minimum: 2.1-in x 2.9-in	Half Letter, Letter, Legal, 11 x 17"
Paper size Maximum: 8.5-in x 36-in	Transmission Paper Size (ADF):A5, A4, A3, B5, B4, Half
Daily Duty Cycle: 3,000 sheets	Letter, Letter, Legal, 11 x 17"
Paper Weight: 50 to 209 g/m	Receiving Paper Size : Half Letter, A5, B5, A4, Letter,
Consumables: Roller assembly kit: 100,000 cycles	Legal, B4, 11 x 17", A3, A3+
General: Operating Systems: Windows 10	Speed Dial / Group Dial : Up to 200 numbers, 199
Temperature: 4 to 95 F (10 to 35 C)	groups
Humidity: 10 â <sup>m</sup> 80% (no condensation)	Fax Features: PC Fax (Transmission/Receive),
Dimensions: 11.7-in x 6-in x 6.1-in (W x D x H)	Automatic Redial, Address book, Broadcast Fax (Mono
Weight: 5.5 lb	Only), Transmit Reservation, Polling Reception, Fax
Connectivity:	Preview, Memory reception, Fax to Email, Fax to
Standard Connectivity:	Folder, Automatic 2-sided Fax
Hi-Speed USB 2.0	
Wi-Fi, Wi-Fi Direct, Ethernet	Paper Handling:
	Number of Paper Trays: 3 (Front 2, Rear 1)
	Standard Paper Input Capacity: Cassette 1: 250 sheets
	for A4 Plain paper (80g/m2)
	50 sheets for Premium Glossy Photo Paper
	Cassette 2: 250 sheets for A4 Plain paper (80 g/m2)
	Rear Slot: 50 sheets for A4 Plain paper (80 g/m2), 20
	sheets for Premium Glossy Photo Paper
	Output Capacity:125 sheets for A4 Plain paper (80
	g/m2), 20 sheets for Premium Glossy Photo Paper
	Maximum Paper Size:329 x 6000 mm
	Paper Sizes: A3, Super B (13 x 19"), Indian Legal,
	Letter, A4, 16K (195 x 270mm), 8K (270 x 390mm),
	Letter, M4, TOK (133 X 2/011111), OK (2/0 X 39011111),



MAIN CAMPUS San Roque, Sogod, Southern Leyte Email: president@southernleytestateu.edu.ph Website: www.southernleytestateu.edu.ph

Excellence | Service | Leadership and Good Governance | Innovation | Social Responsibility | Integrity | Professionalism | Spirituality

Executive (7.25 x 10.5"), B4, B5, A5, B6, A6, 8.5 x 13", 5 x 7", 4 x 6", 8 x 10", Legal (8.5 x 14"), 16:9 wide, Envelopes: #10, DL, C6, C4 Paper Feed Method: Friction feed Print Margin:3mm top, left, right, bottom via custom settings in printer driver Interface: **USB: USB 2.0** Network: Ethernet, Wi-Fi IEEE 802.11 b/g/n, Wi-Fi Direct Network Protocol: TCP/IPv4, TCP/IPv6 Network Management Protocols: SNMP, HTTP, DHCP, BOOTP, APIPA, PING, DDNS, mDNS, SNTP, SLP, WSD, LLTD LCD Screen:4.3" Colour LCD Touch Screen

#### SLCC TEMPLATE

Procuring Entity: SOUTHERN LEYTE STATE UNIVERSITY

Name of the Project: Supply, Delivery & Installation of Various ICT Equipment and Peripherals Location of the Project: Southern Leyte State University - Main Campus, San Roque, Sogod, Southern Leyte

#### STATEMENT OF SINGLE LARGEST COMPLETED CONTRACTS (SLCC) in the last five (5) years

Business Name: Business Address:

Name of Contract	a. Owner Name b. Address Nature of Work c. Telephone Nos.	Contractor's F	Role		a. Date Awarded b. Contract Effectivity	
		Description	%	<ul> <li>b. Amount of Completion</li> <li>c. Duration</li> </ul>	c. Date Completed	
Government						
Private						

Note: This statement shall be supported with:

1. Contract 2. CPES rating sheets and/or Certificate of Completion

3. Certificate of Acceptance

Submitted by:		
	(Printed Name & Signature)	
Designation:		

ignation: Date:

4



MAIN CAMPUS San Roque, Sogod, Southern Leyte Email: <u>president@southernleytestateu.edu.ph</u> Website: www.southernleytestateu.edu.ph

Excellence | Service | Leadership and Good Governance | Innovation | Social Responsibility | Integrity | Professionalism | Spirituality

### NFCC TEMPLATE

### NFCC COMPUTATION FOR ELIGIBILITY CHECK

A. Summary of the Applicant Supplier's/Distributor's/Manufacturer's assets and liabilities on the basis of the attached income tax return and audited financial statement, stamped "RECEIVED" by the Bureau of Internal Revenue or BIR authorized collecting agent, for the immediately preceding year and a certified copyof Schedule of Fixed Assets particularly the list of construction equipment.

		Year 20
1.	Total Assets	
2.	Current Assets	
3.	Total Liabilities	
4.	Current Liabilities	
5.	Net Worth(1-3)	
6.	Net Working Capital(2-4)	

B. The Net Financial Contracting Capacity (NFCC) based on the above data is computedas follows:

NFCC= [(Current assets minus current liabilities) (15)] minus the value of all outstanding or uncompleted portions of the projects underongoing contracts, including awarded contracts yet to be started, conciding with the contract to be bid.

The values of the domestic bidder's current assets and current liabilities shall be based on the latest Audited Financial Statements (AFS) submitted to the BIR.

The Bidder shall attach the AFS to the NFCC Computation for Eligibility Check Form.

NFCC=₽

Submitted by:

Name of Supplier/Distributor/Manufacturer

Signature of Authorized Representative

Date:\_\_\_\_\_

5



MAIN CAMPUS San Roque, Sogod, Southern Leyte Email: <u>president@southernleytestateu.edu.ph</u> Website: www.southernleytestateu.edu.ph

Excellence | Service | Leadership and Good Governance | Innovation | Social Responsibility | Integrity | Professionalism | Spirituality

Issued on  $8^{\rm th}$  day of June 2022 at Southern Leyte State University – Main Campus, Sogod, Southern Leyte.

For guidance and information of all concerned.

*(SIGNED)* MABEL R. CALVA, MPA BAC Chairperson

6